


## Kabelwartels Progress® messing



### Korte metrische stap

#### Type goedkeuring Progress MS

- Lange tweedelige dichting
- Volledig isolerend

|                            |                            |
|----------------------------|----------------------------|
| <b>Artikelnr.:</b>         | <b>1060.25</b>             |
| EAN:                       | 7611614105420              |
| Materiaal                  | Messing vernikkeld         |
| Dichting                   | TPE                        |
| O-ring                     | NBR                        |
| Bedrijfstemperatuur        | -40°C / +100°C             |
| Trekontlasting             | Ausführung A nach EN 62444 |
| Beschermingsklasse         | IP 68 (bis 10 bar) / IP 69 |
| NEMA Type rating           | 4X                         |
| Schroefdraad               | M25x1.5                    |
| Klemmbereik mit Inlet min. | 12.5 mm                    |
| Klemmbereik mit Inlet max. | 16.0 mm                    |
| Minimaal klemmbereik       | 16.0 mm                    |
| Maximaal klemmbereik       | 19.0 mm                    |
| Sleutelbreedte             | 30 mm                      |
| Massawaarde H              | 28 mm                      |
| Schroefdraadlengte L       | 7 mm                       |
| UL - klemmbereik           | 14.5-16.0 mm               |
| Verzending                 | 25                         |

Verkrijgbaar met dichtingselement volgens EN 45545 / NFPA 130. Gelieve bij informatieverzoeken of bestellingen een F voor het artikelnummer te plaatsen.